

02/24/00

02-25-00

X

LERNER AND GREENBERG, P.A.

PATENT ATTORNEYS AND ATTORNEYS AT LAW

2200 Hollywood Boulevard
Hollywood, Florida 33020
Tel: (954) 925-1100
Fax: (954) 925-1101

Herbert L. Lerner (NY Bar)
Laurence A. Greenberg (FL Bar)

Werner H. Stemer (FL Bar), Senior Attorney

Ralph E. Locher (FL, IL, MO Bars)
Manfred Beck (US & German Pat. Agent)
Mark P. Weichselbaum (TN Bar)
Gregory L. Mayback (FL Bar)
Markus Nolff (FL Bar)
Otto S. Kauder (Reg. Pat. Agent)
Adam A. Jorgensen (Reg. Pat. Agent)

www.patentusa.com
patents@patentusa.com

Mailing Address:
Post Office Box 2480
Hollywood, FL 33022-2480

New York Office
153 E 57th Street
Suite 15G
New York, NY 10022

"Express Mail" mailing label number EL080657924US
Date of Deposit February 24, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Docket No.: GR 99 P 4036 US


ALEXIA VRAHAMIS

Date: February 24, 2000

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Enclosed herewith are the necessary papers for filing the following application for Letters Patent:

Applicant : ALFRED RAST et al.

Title : ELECTRO-OPTICAL MODULE


1 sheet of formal drawings in triplicate.

A check in the amount of \$ 690.00 covering the filing fee.

This application is being filed without a signed oath or declaration under the provisions of 37 CFR 1.53(d). Applicants await notification of the date by which the oath or declaration and the surcharge are due, pursuant to this rule.

The Patent and Trademark Office is hereby given authority to charge Deposit Account No. 12-1099 of Lerner and Greenberg, P.A. for any fees due or deficiencies of payments made for any purpose during the pendency of the above-identified application.

Respectfully submitted,


For Applicants

LAURENCE A. GREENBERG
REG. NO. 29,308

LAG:kc

U.S. PTO
09/511815
02/24/00

ELECTRO-OPTICAL MODULE

5 Background of the Invention:

Field of the Invention:

The invention is in the field of optical data transmission and relates to the connection of a fiber optic waveguide segment to an electro-optical module. Such fiber optic waveguide

10 segments are also called pigtailed and are intended for transmitting optical signals to or from the module in order to couple the module optically with another component. The other component can be another module, for example, or also a connector plug of a fiber optic connection cable or a trunk
15 cable.

The invention relates in particular to an electro-optical module with a module body containing an electro-optical converter and a connector that accommodates one end of a fiber
20 optic segment and can be connected for an optical connection of this end with an optical connector interface on the module body side.

The term "electro-optical converter" is to be interpreted,
25 within the scope of the invention, as a component that emits optical signals (light signals in the range of 400 nm to

1500 nm, for example) in response to an electric control. Such a component is also called optical transmitter in the following. The term "electro-optical converter" also means a component that converts optical signals into the corresponding electrical signals. Such a component is also referred to as optical receiver.

A module of the above-mentioned type is described in the Published European Patent Application EP 0 573 941 A1. In accordance with the conventional architecture, such a module includes a module body with a module housing. The module body may also be formed of an injection molding body in accordance with a more modern configuration. The module body of the module includes in its interior at least one electro-optical converter and has a multitude of connectors projecting from its narrow longitudinal sides or its bottom side. The module sides are named for the purpose of this invention on the basis of the respective function location or installation position of the carrier printed circuit board. At one narrow front side of the module, a connector is provided which accommodates one end of the fiber optic segment ("pigtail"), which is ready for a coupling. The connector is held at the narrow front side in the manner that the end of the fiber optic segment is aligned for an optical coupling with the corresponding connector interface on the module body side. The connector interface can be, for example, provided in a receptacle sleeve and be

located in a direct, straight optical connection path between the converter and the end of the fiber optic waveguide segment. The interface can also include a so-called region of free beam propagation between the end of the fiber optic waveguide and the converter.

The injection molding process for manufacturing the module body can damage the fiber optic waveguide due to the generated heat. Also, during a module installation, the required soldering of the connector contacts to the electrical signal input lines or the signal output lines on a carrier printed circuit board can damage the fiber optic waveguide due to the generated heat. For this reason, Published European Patent Application EP 0 573 941 A1 teaches that the connector having the fiber optic waveguide segment is to be connected with the connector interface of the module body only after the injection molding process is completed.

For mounting the module on the carrier printed circuit board, space is needed for the fiber optic waveguide segment, which extends in a horizontal direction. If the connection of the fiber optic segment with the module body is accomplished only after mounting the module body on a carrier printed circuit board, for example, additional space is needed in the area of the module body for handling and accomplishing the connection.

Summary of the Invention:

It is accordingly an object of the invention to provide an electro-optical module which overcomes the above-mentioned disadvantages of the heretofore-known electro-optical modules of this general type and which has a fiber optic waveguide segment ("pigtail") that can be connected subsequently. In particular, it is an object of the invention to provide an electro-optical module which allows to place or install additional electronic and other components in its immediate vicinity on a carrier printed circuit board.

With the foregoing and other objects in view there is provided, in accordance with the invention, an electro-optical module configuration, including an electro-optical module having:

a module body having a top side;

an optical connector interface disposed at the top side of the module body;

an electro-optical converter disposed in the module body;

a fiber optic waveguide segment having an end region; and

a connector accommodating the end region of the fiber optic waveguide segment, the connector being connectable to the optical connector interface for optically connecting the end region.

5

In other words, the object of the invention is achieved in that the connector interface is formed at the top side of the module body. An essential aspect of the module of the invention is, therefore, that the fiber optic waveguide

10 segment can be adjusted and attached in the area of the top side (in an installation position thus on the rear side) of the module body. The fiber optic waveguide segment is to be connected only after the completion of the module body and, if necessary, can later be removed again. The fiber optic
15 waveguide segment and the connector are located at an adequate height, for example at a sufficient height above the surface of the carrier printed circuit board, after the connection has been made, so that additional optical components can be installed or placed in the immediate vicinity of the module.

20 This is especially advantageous when modules operated at a high frequency are used and when optical receivers are connected, because the pre-amplifier provided for an operation of the receiver should be provided in the immediate spatial vicinity of the receiver for reasons of an improved processing
25 of signals.

In accordance with an another feature of the invention, the connector is connected with catch elements or detent elements to the module body. This is advantageous with regard to installation and especially for a possible removal of the
 5 connector from the module body.

In accordance with a further feature of the invention, the connector and the fiber optic waveguide segment projecting from the connector extend at a height of more than 3 mm above
 10 the bottom side of the module. Such a height allows sufficient space in practical applications of the module.

In accordance with a further advantageous feature of the invention, the module is configured as a surface mountable
 15 module.

In order to lead the fiber optic waveguide parallel to the surface of a carrier printed circuit board and parallel to the top side of the module, respectively, a preferred embodiment
 20 of the invented module provides that the connector interface includes a beam deflector that deflects the beam between the converter and the end of the fiber optic segment, which is oriented horizontally in its mounted position.

25 Other features which are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is illustrated and described herein as embodied in an electro-optical module, it is nevertheless not intended to be limited to the details shown, since various
5 modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention,
10 however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

15 Brief Description of the Drawings:

Fig. 1 is an enlarged perspective view of the module according to the invention;

Fig. 2 is a side elevational view of the module body shown in
20 Fig. 1; and

Fig. 3 is a top view of the module body shown in Fig. 1.

Description of the Preferred Embodiments:

25 Referring now to the figures of the drawings in detail and first, particularly, to Fig. 1 thereof, there is shown a

module including a module body 1 and a connector 2. The connector and the module body are shown in Fig. 1 in a state prior to the assembly, when they are still in a separated state. The module body 1 contains an electro-optical converter 3, which is schematically indicated with dotted lines. The converter may be a transmitter in this exemplary embodiment, but can of course also be a receiver. In response to an electric control, the converter 3 generates light signals 6 in the area of an optically active zone 4. The light signals are transmitted vertically upward to the top side 8 of the module.

The module top side 8 has a connector interface 20 in a mechanical coupling block 10 with receptacle grooves 12, 14 running along lateral sides. The receptacle grooves 12, 14 are intended for guiding and fixing the catch arms 16, 17 of the connector 2. A plug pin 22 of the connector can be inserted in the coupling block 10.

One end 24 of a fiber optic waveguide segment 26 is terminated with the front side 23 of the plug pin 22. When inserted, the end 24 is aligned with the optical connector interface 20. The connector interface 20 includes in its interior a deflector mirror surface 30 that is disposed at an inclination or slant 31 in the inner side and at which the emitted beam 6 is deflected by 90° in the direction of the arrow A. The geometrical configuration and the deflection are dimensioned

such that an optical path between the end 24 and the converter 3 is formed with a high optical coupling quality or coupling efficiency.

- 5 The connector interface 20 is easily accessible from the outside due to the way it is installed and integrates the guide function for the plug pin 22.

As shown in Figs. 2 and 3, the grooves (Fig. 2 shows only
10 groove 12) of the mounting block 10 are provided in a manner that a sufficient mounting and connecting clearance h of at least 3 mm for the connector 2 (Fig. 1) is provided for the installation of additional components in the immediate vicinity of the module body. In this manner, additional
15 electronic components - for signal processing, for example - can be placed or mounted in the immediate vicinity of the converter contained in the module body 1. As Figs. 2 and 3 additionally illustrate, the connector contacts 35 projecting from the narrow side surfaces of the module body 1 are
20 configured or suited for surface mounting. When the module body 1 is mounted on a carrier printed circuit board 40, which is only partially shown, the underside or the bottom side 41 of the module faces the surface 42 of the carrier printed circuit board 40 directly. The top side or rear side 8 of the
25 module is consequently facing away from carrier printed circuit board 40.

We claim:

1. An electro-optical module configuration, comprising:

an electro-optical module including:

a module body having a top side;

an optical connector interface disposed at said top side of said module body;

an electro-optical converter disposed in said module body;

a fiber optic waveguide segment having an end region; and

a connector accommodating said end region of said fiber optic waveguide segment, said connector being connectable to said optical connector interface for optically connecting said end region.

2. The electro-optical module configuration according to claim 1, wherein said connector includes catch elements for connecting said connector to said module body.

3. The electro-optical module configuration according to claim 1, wherein:

said electro-optical module has a bottom side;

said fiber optic wave guide segment has a region projecting from said connector; and

said connector and said region of said fiber optic waveguide segment projecting from said connector extend at a height of more than 3 mm above said bottom side of said electro-optical module.

4. The electro-optical module configuration according to claim 1, wherein said electro-optical module is configured as a surface-mountable module.

5. The electro-optical module configuration according to claim 1, wherein said end region of said fiber optic waveguide segment is oriented essentially horizontally in a mounted state, and said optical connector interface includes a beam deflector for deflecting a beam path between said electro-optical converter and said end region of said fiber optic waveguide segment.

6. In combination with a printed circuit board having a surface, an electro-optical module, comprising:

a module body having a top side;

an optical connector interface disposed at said top side of said module body;

an electro-optical converter disposed in said module body;

a fiber optic waveguide segment having an end region;

a connector accommodating said end region of said fiber optic waveguide segment, said connector being connectable to said optical connector interface for optically connecting said end region;




said end region of said fiber optic waveguide segment, in a mounted state, being oriented essentially parallel to the surface of the printed circuit board; and

said optical connector interface including a beam deflector for deflecting a beam path between said electro-optical converter and said end region of said fiber optic waveguide segment.

Abstract of the Disclosure:

An electro-optical module includes a connector and a module body having an electro-optical converter. The connector accommodates one end of a fiber optic waveguide segment and aligns it with the optical connector interface at the side of the module body. The connector interface is provided at the top side of the module body.

MB/tg



COMBINED DECLARATION AND POWER OF ATTORNEY
IN ORIGINAL APPLICATION

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ELECTRO-OPTICAL MODULE

described and claimed in the specification bearing that title, that I understand the content of the specification, that I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve month prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application under 37 C.F.R. 1.56a, and that no application for patent or inventor's certificate of this invention has been filed earlier than the following in any country foreign to the United States prior to this application by me or my legal representatives or assigns:

German Application No. 199 10 164.7, filed February 24, 1999, the International Priority of which is claimed under 35 U.S.C. §119.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

HERBERT L. LERNER (Reg.No.20,435)
LAURENCE A. GREENBERG (Reg.No.29,308)
WERNER H. STEMER (Reg.No.34,956)
RALPH E. LOCHER (Reg.No. 41,947)

Address all correspondence and telephone calls to:

LERNER AND GREENBERG, P.A.
POST OFFICE BOX 2480
HOLLYWOOD, FLORIDA 33022-2480
Tel: (954) 925-1100
Fax: (954) 925-1101

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST JOINT INVENTOR: ALFRED RAST

INVENTOR'S SIGNATURE: _____

DATE: _____

Residence: REGENSTAUF, GERMANY

Country of Citizenship: GERMANY

Post Office Address: ULMENSTRASSE 5
D-93128 REGENSTAUF
GERMANY

FULL NAME OF SECOND JOINT INVENTOR: GERHARD KUHN

INVENTOR'S SIGNATURE: _____

DATE: _____

Residence: KOEFERING, GERMANY

Country of Citizenship: GERMANY

Post Office Address: AM BAHNHOF 11A
D-93096 KOEFERING
GERMANY
